



TEAM "K"



GALVANIZED HOT DIPPED STEEL PROFILES FOR GYPSUM BOARD

LENGTH ON REQUEST

EUROPEAN TEST **CE** EN 13964:2004 - EN 14195:2005 "FIRST STEEL"

TYPE	PROFILES	DESCRIPTION	TYPE	PROFILES	DESCRIPTION
G50		CHANNEL TRACK FOR WALLS mm. 50 Galvanized steel 0,6 mm. 40x50x40 standard length mm. 3000	M75		VERTICAL STUD FOR WALLS mm. 75 Galvanized steel 0,6 mm. 50x73.8x47 standard length mm. 3000
G55		CHANNEL TRACK FOR WALLS mm. 55 Galvanized steel 0,6 mm. 40x55x40 standard length mm. 3000	M100		VERTICAL STUD FOR WALLS mm. 100 Galvanized steel 0,6 mm. 50x98.8x47 standard length mm. 3000
G75		CHANNEL TRACK FOR WALLS mm. 75 Galvanized steel 0,6 mm. 40x75x40 standard length mm. 3000	L3030 L4030		WALL ANGLE PROFILE "L" SECTION mm. 30x30 - mm 40x30 Ribbed surface Galvanized steel 0,6 standard length mm. 3000
G100		CHANNEL TRACK FOR WALLS mm. 100 Galvanized steel 0,6 mm. 40x100x40 standard length mm. 3000	U28 U16		WALL EDGE "U" PROFILE "U" SECTION mm. 30x28 - mm 30x16 Galvanized steel 0,6 mm. 30x28.8x30 - mm. 30x16x30 standard length mm. 3000
PC27-A PC27-S		SUPPORTING MAIN RUNNER FOR CEILINGS mm. 50 Galvanized steel 0,6 mm. 27x48x27 round angles - sharp angles standard length mm. 3000	PAR 30		COVER CORNER PROFILE FOR WALLS Perforated ribbed surface Galvanized steel 0,6 mm. 30x30 standard length mm. 3000
PC15-A PC15-S		SUPPORTING SLIM MAIN RUNNER FOR CEILINGS mm. 50 Galvanized steel 0,6 mm. 15x48x15 round angles - sharp angles standard length mm. 3000	C23		COVER EDGES Galvanized steel 0,6 mm. 14x23 standard length mm. 3000
PS	 thickness mm. 0,7	PRIMARY MAIN CLICK RUNNER FOR PC 27-A 40x28 Galvanized steel 0,7 mm. 40x28x40 standard length mm. 4000	PARAFLEX		COVER CORNER FLEX PROFILE Galvanized steel 0,6 mm. 25x36 standard length mm. 3000
GPS		METAL SNAP ADJUSTMENT FOR SUSPENSION OF MAIN RUNNER CLICK PROFILE TYPE PS	COPRIFLEX		COVER EDGES FLEX PROFILE Prepainted white mm. 14x23 standard length mm. 3000
M50		VERTICAL STUD FOR WALLS mm. 50 Galvanized steel 0,6 mm. 50x48.8x47 standard length mm. 3000	 "U" PROFILE FLEX TYPE UFLEX28 mm. 28x30 LENGTH mm. 3000 "U" PROFILE FLEX TYPE GFLEX50 mm. 50x40 LENGTH mm. 3000 "U" PROFILE FLEX TYPE GFLEX75 mm. 75x40 LENGTH mm. 3000		
M55		VERTICAL STUD FOR WALLS mm. 55 Galvanized steel 0,6 mm. 50x53.8x47 standard length mm. 3000	 "L" PROFILE FLEX TYPE LFLEX75 mm. 75x40 LENGTH mm. 3000 "L" PROFILE FLEX TYPE LFLEX50 mm. 50x40 LENGTH mm. 3000 TYPE PARVAR PERFORATED CORNER PROFILE VARIABLES ANGLE 180° LENGTH mm. 3000		

- All profiles are rollformed from hot dipped 1st galvanized steel DX51DZ
- All profiles are tested and certified EN-ASTM
- Extra standard lengths: can be customized upon customer request

METALSCREEN® S.p.A. - Via Aldo Moro, 38 - 41030 Bompporto (MO) - Italy EU - Tel. +39 059/8170611 - Fax +39 059/8170633
e-mail: metalscreen@metalscreen.it - www.metalscreen.it